



EZ3007 Fluoride Analyser

Kat. číslo produktu: **EZ3007.XXXXXXXXXX**
EUR Cena bez DPH: Kontaktujte nás

Online ion-selective Fluoride measurements in industrial and environmental applications

ISE technology for optimal analytical performance

With limited maintenance requirements and reduced reagent consumption, the EZ3000 Series are the ideal choice for a wide range of water monitoring applications where ion-selective electrodes are the preferred analytical technique. Outstanding precision and stability is guaranteed by the temperature-controlled measurement.

Direct, discontinuous ISE method

Contrary to separate electrodes or other analysers in the market, the EZ3000 Series does not run a continuous measurement. The principle of discontinuous ISE analysis not only enhances control over conversion of ion activity to electric potential, it also eliminates risk of cross-contamination between cycles and reduces overall consumption of reagents.

The EZ3000 Series combine unique ISE technology with a set of analysis, control and communication features in an industrial analyser mainframe with designed for the highest performance:

- Automatic direct ion-selective measurements
- Smart automatic features
- Control and communication via industrial panel PC
- Standard 4 - 20 mA signal output with alarm processing
- Communication ports supporting connectivity to Modbus
- Multiple stream analysis
- Reduced reagent consumption

There are many additional options available. Please contact Hach for more details.

Technické údaje

Alarm:	1x malfunctioning, 4x user-configurable, max. 24 VDC/0.5 A, potential free contacts
Analógové výstupy:	Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)
Automatické čistenie:	Áno

Č. prúdov vzoriek:	1, 2, 4 or 8
Certifikácia:	CE compliant / UL certified
Demineralised water:	For rinsing
Detekčný limit:	≤ 0.1 mg/L
Digitálne výstupy:	Optional: Modbus (TCP/IP, RS485)
Doba cyklu :	5 minutes
Earth connection:	Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm²
Hmotnosť:	25 kg
Instrument air:	Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air
Interferencie:	Metal ions like aluminium > 72 mg/L, calcium > 108 mg/L and iron > 150 mg/L. Fats, oil, proteins, surfactants and tar.
Kalibrácia:	Automatic, 2-point; frequency freely programmable
Kvalita vzorky:	Maximum particle size 100 µm, < 0.1 g/L; Turbidity < 50 NTU
Materiál:	Hinged part: Thermoform ABS, door: PMMA
	Wall section: Galvanised steel, powder coated
Metóda merania:	Discontinuous, direct measurement by combined ion-selective electrode, conform with standard methods EPA 9214 and ASTM D1179
Model:	EZ3007
Napájanie:	100 - 240 VAC, 50/60 Hz
	Max. power consumption: 120 VA
Obsah balenia:	EZ3007 Fluoride Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 1 x ISE Fluoride Electrode and 1 x empty 2.5L Reagent Container with Fittings (for Buffer Solution)
Odtok:	Atmospheric pressure, vented, min. Ø 32 mm
Parameter:	Fluoride
Presnosť:	Better than 2% full scale range for standard test solutions
Reagent Requirements:	Keep between 10 - 30 °C
Rozmery (V x Š x H):	690 mm x 465 mm x 330 mm
Rozsah merania:	1 - 10 mg/L F ⁻
	Optional:
	0.25 - 2.5 mg/L F ⁻
	0.5 - 5 mg/L F ⁻
Rýchlosť prietoku vzorky:	100 - 300 mL/min
Teplota prostredia:	10 - 30 °C ±4 °C deviation at 5 - 95% relative humidity (non-condensing)
Teplota vzorky:	10 - 30 °C
Trieda ochrany:	Protection class: Analyser cabinet: IP44 / Panel PC: IP65
Validation:	Automatic; frequency freely programmable
Vzorka: tlak:	By external overflow vessel
Záruka:	24 mesiacov
Zdroj napájania:	100 - 240 VAC, 50/60 Hz

Obsah balenia

EZ3007 Fluoride Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 1 x ISE Fluoride Electrode and 1 x empty 2.5L Reagent Container with Fittings (for Buffer Solution)